



**DAIRYPRO**  
Your Productivity Partner

## Manure Management Systems

All components available, including Pumps, Separators, Mixers

### Submersible Motor Manure Pump 4,0 kW CSP/EU 4,0kW/ 400V/ 50Hz

- submersible motor pump with adjust device (CSP)
- spiral housing and suction bell iron
- CSP: Impeller and cutting disc made of steel
- pump shaft made of stainless-steel ball bearing
- motor temperature class H, with tr resistor 150° C, for thermic winding protection
- leakage sensor extends into oil re (additional motor protection)



### Manure Separator S300 kpl.

- Auger and screen made of stainless steel
- Screen sizes to choose: 0.25 / 0.50 / 0.75 mm
- Housing of cast iron
- Discharge flaps of stainless steel, with 2 weights
- Mounting frame of galvanized Steel



### Mixer MEX 305/4,5/7,5/400/50 electric mixer 4,5m - with motor 7,5kW / 400 / 690V / 50Hz

- closed E-motor with star-delta reversing switch 7,5 kW (10HP), 380-440 V, 50Hz
- mixing rod with multiple-bearing drive shaft running in oil bath
- 1450 rpm mixer blade with guard bow
- minimum pit opening: 60 x 60 cm without mixer trolley

